

Ringleader ASGD: The First Asynchronous SGD with Optimal Time Complexity under Data Heterogeneity

Artavazd Maranjyan

Mathematics and Applications Colloquium
KAUST, 28 October 2025



جامعة الملك عبد الله
للعلوم والتقنية
King Abdullah University of
Science and Technology



AI = Optimization

$$\underset{x \in \mathbb{R}^d}{\text{minimize}} \{ f(x) := \mathbb{E}_{\xi \sim \mathcal{D}} [f(x; \xi)] \}$$

Model parameters
we want to find

The distribution of
the training dataset

$$f(x; \xi) := \text{Loss} (\text{Model} (x; \xi^{\text{input}}) , \xi^{\text{label}})$$

Distributed Learning



$\mathcal{D}_1$

$$f_1(x) := \mathbb{E}_{\xi_1 \sim \mathcal{D}_1} [f_1(x; \xi_1)]$$



$\mathcal{D}_2$

$$f_2(x) := \mathbb{E}_{\xi_2 \sim \mathcal{D}_2} [f_2(x; \xi_2)]$$



$\mathcal{D}_3$


$$f_3(x) := \mathbb{E}_{\xi_3 \sim \mathcal{D}_3} [f_3(x; \xi_3)]$$

$$\underset{x \in \mathbb{R}^d}{\text{minimize}} \left\{ f(x) := \frac{1}{n} \sum_{i=1}^n f_i(x) \right\}$$



Server

A common method in ML is Stochastic Gradient Descent (SGD)



Stepsize / Learning rate

$$x^{k+1} = x^k - \gamma g(x^k)$$

Unbiased gradient estimator, i.e.

$$\mathbb{E} [g(x^k)] = \nabla f(x^k)$$


$$g(x^k) = \frac{1}{n} \sum_{i=1}^n \nabla f_i(x^k; \xi_i^k)$$

How to parallelize SGD in heterogeneous systems?




$$\nabla f_1(x; \xi_1)$$

Compute time = τ_1




$$\nabla f_2(x; \xi_2)$$

Compute time = τ_2



$$\nabla f_3(x; \xi_3)$$


Compute time = τ_3



Server


Client Compute Heterogeneity is Real

An LSTM-based language model
on nearly 100 million Android phones.



Minibatch SGD:


Each worker does one job only



$$x^{k+1} = x^k - \gamma \frac{1}{n} \sum_{i=1}^n \nabla f_i(x^k; \xi_i^k)$$

Asynchronous SGD

Remove the synchronization




The first Asynchronous SGD




B Recht, C Re, S Wright, F Niu (2011)

HOGWILD!: A lock-free approach to parallelizing stochastic gradient descent


Updates of Asynchronous SGD has delayed stochastic gradients



Updates of Asynchronous SGD has delayed stochastic gradients



Updates of Asynchronous SGD has delayed stochastic gradients



Updates of Asynchronous SGD has delayed stochastic gradients

Delay of worker i^k at iteration k

$$x^{k+1} = x^k - \gamma \nabla f_{i^k} \left(x^{k-\delta_{i^k}^k}; \xi^{k-\delta_{i^k}^k} \right)$$

Uses a gradient from a single worker

Similarity assumption


$$\|\nabla f_i(x) - \nabla f(x)\| \leq \zeta$$



Server

Asynchronous SGD can get wild:
delays can degrade performance


$$f(x, y) = x^2 + 5y^2$$



Asynchronous SGD can get wild: delays can degrade performance

Gradient Descent iterations


$$f(x, y) = x^2 + 5y^2$$



Asynchronous SGD can get wild: delays can degrade performance

$$f(x, y) = x^2 + 5y^2$$


Delay = 5




Asynchronous SGD can get wild: delays can degrade performance

$$f(x, y) = x^2 + 5y^2$$

Delay = 5




Back to Synchrony: Malenia SGD




$$x^{k+1} = x^k - \gamma \frac{1}{n} \sum_{i=1}^n \frac{1}{b_i^k} \sum_{j=1}^{b_i^k} \nabla f_i(x^k; \xi_i^{k,j})$$

Malenia SGD with Gradient Table




$$b \quad 0 \quad 0 \quad 0$$
$$\left[\begin{array}{c} \\ \\ \\ \end{array} \right]$$

Malenia SGD with Gradient Table



$$b \quad \begin{matrix} 1 & 0 & 0 \\ \left[\begin{array}{c} G_1 \end{array} \right] \end{matrix}$$
$$G_1 = \nabla f_1 \left(x^0; \xi_1^{0,1} \right)$$

Malenia SGD with Gradient Table




b 1 1 0

$$\begin{bmatrix} \text{green line} & \text{orange line} \\ G_1 & G_2 \end{bmatrix}$$

$$G_2 = \nabla f_2 \left(x^0; \xi_2^{0,1} \right)$$

Malenia SGD with Gradient Table




$$b \quad \begin{matrix} 2 & 1 & 0 \end{matrix}$$

$$\left[\begin{array}{c} \text{green line} \\ G_1 \\ \text{green line} \end{array} \quad \begin{array}{c} \text{orange line} \\ G_2 \\ \text{orange line} \end{array} \right]$$

$$G_1 = \sum_{j=1}^2 \nabla f_1 \left(x^0; \xi_1^{0,j} \right)$$

Malenia SGD with Gradient Table



Discard!


$$x^1 = x^0 - \gamma \frac{1}{n} \sum_{i=1}^n \frac{G_i}{b_i}$$

$$b \quad \begin{matrix} 2 & 1 & 1 \end{matrix}$$


$$\left[\begin{array}{c|c|c} \text{green} & \text{orange} & \text{red} \\ G_1 & G_2 & G_3 \end{array} \right]$$

$$G_3 = \nabla f_3 \left(x^0; \xi_3^{0,1} \right)$$


Malenia SGD with Gradient Table



Can we achieve optimal time complexity with asynchronous methods?



Yes — **Ringleader ASGD** can:
Make It Less Wild



Yes — **Ringleader ASGD** can: Make It Less Wild

Phase 1 (collect)


Wait to receive at least one
gradient from each worker

Phase 2 (update)

Perform a single update per worker




Ringleader ASGD: Phase 1 (collect)




$$\begin{bmatrix} b & 0 & 0 & 0 \end{bmatrix}$$

Ringleader ASGD: Phase 1 (collect)



$$b \quad \begin{bmatrix} 1 & 0 & 0 \\ G_1 \end{bmatrix}$$
$$G_1 = \nabla f_1 \left(x^0; \xi_1^{0,1} \right)$$

Ringleader ASGD: Phase 1 (collect)




b 1 1 0

$$\begin{bmatrix} \text{green line} & \text{orange line} \\ G_1 & G_2 \end{bmatrix}$$

$$G_2 = \nabla f_2 \left(x^0; \xi_2^{0,1} \right)$$


Ringleader ASGD: Phase 1 (collect)




$$\begin{matrix} b & 2 & 1 & 0 \\ \left[\begin{array}{c} \text{green line} \\ G_1 \\ \text{green line} \end{array} & \begin{array}{c} \text{orange line} \\ G_2 \\ \text{orange line} \end{array} & & \right] \end{matrix}$$

$$G_1 = \sum_{j=1}^2 \nabla f_1 \left(x^0; \xi_1^{0,j} \right)$$

Ringleader ASGD: Phase 2 (update)




Ringleader ASGD: Phase 2 (update)




$$G_2 = \sum_{j=1}^2 \nabla f_2 \left(x^0; \xi_2^{0,j} \right)$$

Ringleader ASGD: Phase 2 (update)




Ringleader ASGD: Phase 1 (collect)




$$\begin{bmatrix} 0 & 0 & 0 & b \end{bmatrix}$$

Ringleader ASGD: Phase 1 (collect)




$$\begin{bmatrix} 0 & 0 & 0 & b \end{bmatrix}$$

Ringleader ASGD: Phase 1 (collect)




$$\begin{bmatrix} 1 & 0 & 0 & b \\ G_1 \end{bmatrix}$$
$$G_1 = \nabla f_1 \left(x^3; \xi_1^{3,1} \right)$$

Ringleader ASGD: Phase 1 (collect)



$$\begin{bmatrix} 1 & 0 & 1 & b \\ G_1 & & G_3 & \end{bmatrix}$$
$$G_3 = \nabla f_3 \left(x^1; \xi_3^{1,1} \right)$$

Ringleader ASGD: Phase 2 (update)




$$x^4 = x^3 - \gamma \frac{1}{n} \sum_{i=1}^n \frac{G_i}{b_i}$$

$$\begin{bmatrix} 1 & 1 & 1 \\ G_1 & G_2 & G_3 \end{bmatrix} \quad b$$

$$G_2 = \nabla f_2 \left(x^2; \xi_2^{2,1} \right)$$

Ringleader ASGD: Phase 2 (update)




$$x^5 = x^4 - \gamma \frac{1}{n} \sum_{i=1}^n \frac{G_i}{b_i}$$

$$\begin{bmatrix} 2 & 1 & 1 & b \\ G_1 & G_2 & G_3 \end{bmatrix}$$

$$G_1 = \sum_{j=1}^2 \nabla f_1 \left(x^3; \xi_1^{3,j} \right)$$

Ringleader ASGD: Phase 2 (update)



What to do with this gradient?


$$\left[\begin{array}{c} \text{orange line} \\ G_2^+ \end{array} \right]$$

Store it for later use!

$$G_2^+ = \nabla f_2 \left(x^4; \xi_2^{4,1} \right)$$

$$\left[\begin{array}{cccc} & 2 & 1 & 1 & b \\ & \text{green line} & \text{orange line} & \text{red line} & \\ G_1 & G_2 & G_3 & & \end{array} \right]$$

Ringleader ASGD: Phase 2 (update)



2 1 1 b


$$\left[\begin{array}{c} \text{orange line} \\ G_2^+ \\ \text{orange line} \end{array} \right]$$

Store it for later use!


$$G_2^+ = \nabla f_2 \left(x^4; \xi_2^{4,1} \right)$$

$$\left[\begin{array}{c} \text{green line} \\ G_1 \\ \text{green line} \end{array} \quad \left[\begin{array}{c} \text{orange line} \\ G_2 \\ \text{orange line} \end{array} \right] \quad \left[\begin{array}{c} \text{red line} \\ G_3 \\ \text{red line} \end{array} \right] \right]$$


Ringleader ASGD: Phase 2 (update)




Ringleader ASGD: Phase 2 (update)




Ringleader ASGD: Prepare for the Next Round



Ringleader ASGD: Start with Phase 1




Ringleader ASGD



$$\delta_i^k \leq 2n - 2$$

Ringleader ASGD outperforms existing baselines



Two-layer MLP

MNIST

$n = 100$

$\tau_i = i + |\eta_i|$

$\eta_i \sim \mathcal{N}(0, i)$



KHALAS



More on my PhD Defense
December 4
(Imk if you want to attend)